

1	2	3	4	5																																								
<p>Panel min. 0,8 max. 2,8</p> <p>PANEL LAYOUT - COMPONENT VIEW</p>																																												
<p>TECHNICAL CHARACTERISTICS</p> <p>MATERIAL INSULATOR: PA66G25 FLAMMABILITY RATING: UL94V0 COLOR: BLACK CONTACT / PLATING: COPPER ALLOY / Ni+Sn FUSE CONTACT: PHOSPHOR BRONZE / Ni+Sn SPRING: INOX STEEL</p> <p>ENVIRONMENTAL OPERATING TEMPERATURE: -30°C UP TO +120°C COMPLIANCE: LEAD FREE AND ROHS</p> <p>ELECTRICAL UL VDE CURRENT RATING: 20A 10A WORKING VOLTAGE: 250VAC 250VAC WITHSTANDING VOLTAGE: 1,5KV 3KV RATED POWER ACCEPTANCE: --- PROTECTION CLASS: I o II CONTACT RESISTANCE: 5/10 mΩ MAX</p> <p>STANDARD UL RoHS CERTIFIED: E157417 RoHS CERTIFIED: 133366 CAT. N°: PTF/30 TYPE: PTF/30</p> <p>MECHANICAL FUSE-LINK: 5x20 mm PROTECTION RATE: IP40 SHOCKSAFE CATEGORY: PC1-PC2</p> <p>SOLDERING MANUAL SOLDERING</p> <p>PACKAGING BOX</p>																																												
<p>GENERAL TOLERANCE ±0,1</p>																																												
<p>PROJECTION: </p> <p>APPROVAL: FBr</p>																																												
<p>UNIT: MM SCALE: SHEET: 1/2 DRAW: AK</p>																																												
<p>RoHS Compliant</p> <table border="1"> <tr> <td>G</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>F</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>D</td> <td>29-MAR-17</td> <td>PCN</td> <td>AK</td> <td>BY</td> </tr> <tr> <td>C</td> <td>30-JUN-15</td> <td>SHOCKSAFE</td> <td>AK</td> <td>BY</td> </tr> <tr> <td>B</td> <td>01-APR-15</td> <td>PROTECTION RATE</td> <td>QL</td> <td>BY</td> </tr> <tr> <td>A</td> <td>11-SEP-14</td> <td>PDF</td> <td>AK</td> <td>BY</td> </tr> <tr> <td>REV</td> <td>DATE</td> <td>FILE</td> <td></td> <td></td> </tr> </table>					G					F					E					D	29-MAR-17	PCN	AK	BY	C	30-JUN-15	SHOCKSAFE	AK	BY	B	01-APR-15	PROTECTION RATE	QL	BY	A	11-SEP-14	PDF	AK	BY	REV	DATE	FILE		
G																																												
F																																												
E																																												
D	29-MAR-17	PCN	AK	BY																																								
C	30-JUN-15	SHOCKSAFE	AK	BY																																								
B	01-APR-15	PROTECTION RATE	QL	BY																																								
A	11-SEP-14	PDF	AK	BY																																								
REV	DATE	FILE																																										
<p>DESCRIPTION: SHOCKSAFE FUSEHOLDERS - PANEL - SCREW'N LOCK COVER - THT - GLOW WIRE PLASTIC - WR-FSH</p> <p>REFERENCE DF : 515020</p> <p>SIZE A4</p>																																												



Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

D

RoHS Compliant

G

F

E

D

C

B

A
10-SEP-14REV
DATE

PDF

QL

BY

GENERAL TOLERANCE

.X = \pm 0.2.XX = \pm 0.15

UNIT: MM

SCALE:

SHEET: 2/2

DRAW: QL

PROJECTION:



APPROVAL: JC

DESCRIPTION: DISCLAIMER

REFERENCE DF : 515020

SIZE

A4

