

1	2	3	4	5																
<p>A</p> <p>TECHNICAL CHARACTERISTICS</p> <p>MATERIAL INSULATOR: PA6G30 FLAMMABILITY RATING: UL94HB COLOR: BLACK CONTACT / PLATING: COPPER ALLOY / NI FUSE CONTACT: SPRING: INOX STEEL</p> <p>ENVIRONMENTAL OPERATING TEMPERATURE: -30°C UP TO +120°C COMPLIANCE: LEAD FREE AND ROHS</p> <p>ELECTRICAL CURRENT RATING: 6,3A WORKING VOLTAGE: 250VAC WITHSTANDING VOLTAGE: 1,5KV RATED POWER ACCEPTANCE: 1,6W PROTECTION CLASS: I o II CONTACT RESISTANCE: 5/10 mΩ MAX</p> <p>B</p> <p>MECHANICAL FUSE-LINK: 5x20 mm and 6,3x32 mm PROTECTION RATE: IP00 SHOCKSAFE CATEGORY: PC1</p> <p>PACKAGING BOX</p> <p>C</p>																				
<p>D</p> <p>RoHS Compliant</p> <p>GENERAL TOLERANCE: ±0,1</p> <p>PROJECTION: </p> <p>APPROVAL: QL</p> <table border="1"> <tr> <td>REV</td> <td>DATE</td> <td>FILE</td> <td>BY</td> </tr> <tr> <td>A</td> <td>11-SEP-14</td> <td>PDF</td> <td>AK</td> </tr> <tr> <td>B</td> <td>08-APR-15</td> <td>GENERAL UPDATE</td> <td>AK</td> </tr> <tr> <td>C</td> <td>30-JUN-15</td> <td>SHOCKSAFE</td> <td>AK</td> </tr> </table> <p>UNIT: MM SCALE: 1/2 SHEET: 1/2 DRAW: AK</p> <p>DESCRIPTION: FUSEHOLDER BLOCKS - IN-LINE - TURN'N LOCK COVER - WR-FSH</p> <p>REFERENCE DF : 516045</p> <p>SIZE A4</p>					REV	DATE	FILE	BY	A	11-SEP-14	PDF	AK	B	08-APR-15	GENERAL UPDATE	AK	C	30-JUN-15	SHOCKSAFE	AK
REV	DATE	FILE	BY																	
A	11-SEP-14	PDF	AK																	
B	08-APR-15	GENERAL UPDATE	AK																	
C	30-JUN-15	SHOCKSAFE	AK																	
<p>df Electric</p>																				

Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.


A

B

C

D

RoHS Compliant	
G	
F	
E	
D	
C	
B	
A	10-SEP-14
REV	DATE
	PDF
	FILE
	QL
	BY



PROJECTION:

APPROVAL: JC

GENERAL TOLERANCE

UNIT: MM

SCALE:

SHEET: 2/2

DRAW: QL



DESCRIPTION: DISCLAIMER

REFERENCE DF : 516045

SIZE

A4