


RSP 4

Rated cross-section [mm ²]	4	
Rated current [A]	6,3	
Short-time withstand current [A]	1 500	
Rated voltage U _i [V]	400	
Rated impulse withstand voltage U _{imp} [V]	4 000	
Rated voltage or operating voltage range [V]	250	
Conductor cross section [mm ²]	Solid conductor	0,5 ÷ 6
	Stranded conductor	0,5 ÷ 4
	Finely stranded conductor	0,5 ÷ 4
	2 x Solid conductor, stranded conductor, finely stranded	0,5 ÷ 1,5
	3 x Solid conductor, stranded conductor, finely stranded	0,5 ÷ 1
Maximum conductor connection cross-section, finely stranded with wire-end ferrules with plastic collar [mm ²]	4	
Stripping length [mm]	9,5	
Tightening torque [Nm]	0,5	
Tools	Screwdriver PH 0	
Assembly method (on DIN rail)	TH 15, TH 35, G 32	
Pollution degree	2	
IP code	20 / 10 ¹	
Operating temperature [°C]	-40 ÷ +55	
Number of clamping points per level	2	
Number of levels	1	
End cover plate required	NO	
Maximum scattered power P _{vk} [W]	Independently arrangement	2 W / 6,3 A
	Combined arrangement	1 W / 6,3 A
Size of fuse-link	F, M, T average 5 x 20	
Testing	ČSN EN 60947-7-3	
Dimensions [mm] (width / height / length)	9 / 46,3 / 55	
Weight [g]	15	
Packing [pcs]	25	
Order number	A 631 210	

¹ The protection class of the fuse terminals is IP 20. In case of open fuse holder, the protection is IP 10.



RSP A 4

Rated cross-section [mm ²]	4	
Rated current [A]	12,5	
Short-time withstand current [A]	1 500	
Rated voltage U _i [V]	500	
Rated impulse withstand voltage U _{imp} [V]	4 000	
Rated voltage or operating voltage range [V]	500	
Conductor cross section [mm ²]	Solid conductor [mm ²]	0,5 ÷ 6
	Stranded conductor	0,5 ÷ 4
	Finely stranded conductor	0,5 ÷ 4
	2 x Solid conductor, stranded conductor, finely stranded	0,5 ÷ 1,5
	3 x Solid conductor, stranded conductor, finely stranded	0,5 ÷ 1
Maximum conductor connection cross-section, finely stranded with wire-end ferrules with plastic collar [mm ²]	4	
Tightening torque [Nm]	0,5	
Tools	Screwdriver PH 0	
Assembly method (on DIN rail)	TH 15, TH 35, G32	
Pollution degree	2	
IP code	20 / 10 ¹	
Operating temperature [°C]	-40 ÷ +55	
Number of clamping points per level	2	
Number of levels	1	
End cover plate required	NO	
Maximum scattered power P _{vk} [W]	2	
Size of fuse-link	F, T average 6,3 x 32	
Testing	ČSN EN 60947-7-3	
Dimensions [mm] (width / height / length)	10,5 / 46 / 68,5	
Weight [g]	21	
Packing [pcs]	10	
Order number	1p.	A 631 140
	2p.	-
	3p.	-
	4p.	-
	5p.	-

¹ The protection class of the fuse terminals is IP 20. In case of open fuse holder, the protection is IP 10.