

# SOCLES DE PRISE



230V~  
50/60Hz  
3p=6h  
4p+5p=9h

400V~  
50/60Hz  
3p=9h  
4p+5p=6h



Désignation	In (A)	Pôles	Références		Cond.
<b>SOCLE PRISE DROITE IP44</b>	16	3	<b>313-6</b>	313-9	10
	16	4	314-9	<b>314-6</b>	10
	16	5	315-9	<b>315-6</b>	10
	32	3	<b>323-6</b>	323-9	10
	32	4	324-9	<b>324-6</b>	10
	32	5	325-9	<b>325-6</b>	10



Désignation	In (A)	Pôles	Références		Cond.
<b>SOCLE PRISE INCLINÉE IP44</b>	16	3	<b>413-6</b>	413-9	10
	16	4	414-9	<b>414-6</b>	10
	16	5	415-9	<b>415-6</b>	10
	32	3	<b>423-6</b>	423-9	10
	32	4	424-9	<b>424-6</b>	10
	32	5	425-9	<b>425-6</b>	10



Désignation	In (A)	Pôles	Références		Cond.
<b>SOCLE PRISE DROITE IP66/67</b>	16	3	<b>3132-6</b>	3132-9	10
	16	4	3142-9	3142-6	10
	16	5	3152-9	<b>3152-6</b>	10
	32	3	<b>3232-6</b>	3232-9	10
	32	4	3242-9	3242-6	10
	32	5	3252-9	<b>3252-6</b>	10
	63	5	335-9	335-6	2
	125	5	345-9	<b>345-6</b>	2



Désignation	In (A)	Pôles	Références		Cond.
<b>SOCLE PRISE INCLINÉE IP66/67</b>	16	3	<b>4132-6</b>	4132-9	10
	16	4	4142-9	<b>4142-6</b>	10
	16	5	4152-9	<b>4152-6</b>	10
	32	3	<b>4232-6</b>	4232-9	10
	32	4	4242-9	<b>4242-6</b>	10
	32	5	4252-9	<b>4252-6</b>	10
	63	5	435-9	<b>435-6</b>	2
	125	5	445-9	<b>445-6</b>	2



Désignation	In (A)	Pôles	Références		Cond.
<b>CACHE VIS ARRIÈRE SOCLE CE</b>	16	4	TS167S		50/150
	32	4	TS327S		50/150

• Barrette sectionnable de 4 pôles  
• Positionnement arrière sur chacun des pôles

## DIMENSIONS

Socles IP44	Droit 16A	Droit 32A	Droit 63A	Droit 125A	Incliné 16A	Incliné 32A	Incliné 63A	Incliné 125A
Plastron (mm)	70 x 70	70 x 70	--	--	70 x 85	80 x 97	--	--
Entraxe percages	56 x 56	56 x 56	--	--	50 x 65	60 x 73	--	--

  

Socles IP66/67	Droit 16A	Droit 32A	Droit 63A	Droit 125A	Incliné 16A	Incliné 32A	Incliné 63A	Incliné 125A
Plastron (mm)	75 x 75	75 x 75	100 x 100	120 x 120	92 x 100	92 x 100	100 x 112	120 x 130
Entraxe percages	60 x 60	60 x 60	80 x 80	100 x 100	77 x 85	77 x 85	80 x 88	100 x 108

Autres dimensions disponibles sur simple demande